



HIGH TECH

**GOODYEAR® COMMERCIAL TIRES AND RETREADS
ENGINEERING DATA BOOK**

goodyeartrucktires.com

GOODYEAR
MORE DRIVEN.

Table of Contents

Goodyear Overview	3
Goodyear Total Solution	4
Trusted Products	5
Trusted Products - Product Screen	6
Nationwide Dealer Network	7
Reliable Services	8
Fleet Management Tools	9
Goodyear Technologies	10
Goodyear Product Application Guide	11
Goodyear Product Reference Guide	12-13
Dunlop Product Reference Guide	13
Kelly Product Reference Guide	13

Goodyear

Long Haul

Steer/All Position

Endurance LHS	14
G399A LHS Fuel Max	15
Marathon LHS	16

Drive

Endurance LHD	17
Fuel Max LHD G505D	18
Fuel Max SSD	19
G572 1AD Fuel Max	20
G572A LHD Fuel Max	21
Marathon LHD	22

Trailer

Fuel Max LHT	23
Fuel Max SST	24
Fuel Max T	25
G316 LHT DuraSeal + Fuel Max	26
G316 LHT Fuel Max	27
Marathon LHT	28
Marathon LHT II	29

Regional/Urban

Steer/All Position

Endurance RSA	30
Endurance RSA ULT	31
Fuel Max RSA	32
G159A	33
G291	34
G647 RSS	35
G670 RV MRT	36
G670 RV ULT	37
Marathon RSA	38
Marathon RSS	39
Regional RHS	40

Drive

Endurance RSD ULT	41
Endurance TSD	42
G182 RSD	43
G182 RSD GHG	44
G622 RSD	45
G622 RSD ULT	46
G633 RSD	47
Marathon RSD	48

Trailer

G114 LHT	49
G614 RST	50
G619 RST	51

Mixed Service

Steer/All Position

Endurance WHA	52
Endurance WHA DuraSeal	53
G275 MSA	54
G287 MSA	55
G288 MSA	56
G288 MSA DuraSeal	57
G289 WHA	58
G289 WHA DuraSeal	59
G296 MSA	60
G296 MSA DuraSeal	61

G296 WHA	62
G296 WHA DuraSeal	63
G731 MSA	64
G731 MSA Duraseal	65
G751 MSA	66
G751 MSA Duraseal	67
Workhorse MSA	68

Drive

Armor Max Pro Grade MSD	69
Armor Max Pro Grade MSD DuraSeal	70
G171 LT	71
G177	72
G177 OTR	73
G278 MSD	74
G282 MSD	75
G741 MSD	76
G971 Armor Max	77
Workhorse MSD	78

Dunlop

Regional/Urban

Steer/All Position

SP160	79
-------	----

Drive

SP461	80
-------	----

Mixed Service

Steer/All Position

SP231A	81
SP281	82
SP345	83
SP831	84

Drive

SP881	85
-------	----

Kelly

Long Haul

Steer/All Position

Armorsteel LHS 86

Drive

Armorsteel KDA 87

Armorsteel LHD 88

Trailer

Armorsteel KTSA 89

Armorsteel LHT 90

Regional/Urban**Steer/All Position**

Armorsteel KRH 91

Armorsteel RSA ULT 92

Drive

Armorsteel KDM I 93

Armorsteel RSD ULT 94

Mixed Service**Steer/All Position**

Armorsteel MSA 95

Drive

Armorsteel MSD 96

Load and Inflation Tables 97



COUNT ON THE GLOBALLY TRUSTED LEADER

Goodyear® is one of the best-known tire brands in the industry, and it's more than just an iconic name. It's a brand that stands for reliability, integrity and innovation — a brand that continues to earn the trust of customers again and again.

LEADERS IN INNOVATION

Goodyear's broad experience drives progress across a variety of applications, including consumer, commercial, off-the-road (OTR), aviation and racing tires.



of continual
innovation



of driving
retread quality



around the globe



worldwide and offices
in almost every country

PREFERRED BY FLEETS



of fleet customers
are satisfied with
Goodyear*



of fleet customers
would recommend
Goodyear tires*

*2013 Lieberman Research Worldwide Brand Health Study.



ADVANTAGES FLEETS NEED TO SAVE MONEY

Every fleet needs to lower its operating costs — and Goodyear® makes it possible with its Total Solution. Tires and retreads are just part of the equation.



TRUSTED PRODUCTS

Innovative Products
For Any Fleet Application



NATIONWIDE DEALER NETWORK

2,300+ Dealers In North America
Ready To Help Your Fleet



RELIABLE SERVICES

Most Reliable Nationwide
Roadside Service In
The Industry¹



FLEET MANAGEMENT TOOLS

Tire And Retread Tracking
And Fleet Dashboard

¹Fleet research study, Nov. 2015, Lieberman Research Worldwide, 590-fleet sample. Goodyear Dealer network roadside service compared to Michelin, Bridgestone and Continental.



TIRES AND RETREADS THAT HELP DRIVE FLEET SAVINGS

Goodyear® offers a broad selection of innovative tires and retreads to help improve efficiency for commercial fleets of a wide variety of sizes and applications.

COMMERCIAL APPLICATIONS



Long Haul



Regional







Urban



Mixed Service



TIRES AND RETREADS FOR A WIDE RANGE OF APPLICATIONS

LONG HAUL 	REGIONAL 	URBAN 	MIXED SERVICE 
GOODYEAR FUEL MAX[®]			GOODYEAR ARMOR MAX[®]
GOODYEAR ENDURANCE			
GOODYEAR MARATHON[®]			GOODYEAR WORKHORSE[®]
			DUNLOP[®]
KELLY[®] ARMORSTEEL[®]			



A DEALER NETWORK THAT'S BUILT AROUND FLEETS

The Goodyear® Commercial Tire & Service Network includes 2,300+ locations nationwide. Each location offers consistent products and services from tire professionals who know how to save fleets money. Fleets can turn to any location for these benefits.

THE RIGHT TIRES AND RETREADS

Goodyear Commercial Tire & Service Network members can help fleets choose the right products to help lower their operating costs.

- Commercial and off-the-road products
- Goodyear, Dunlop® and Kelly® brands
- Tires and retreads to help optimize your investment
- Customized recommendations based on your needs

PROFESSIONAL FLEET SERVICES

Goodyear Commercial Tire & Service Network members use state-of-the-art service equipment, and our trained technicians adhere to the Tire Industry Association CTS 200 level for high-quality service at any location.

- 24-hour emergency road service
- 2-hour target roll time
- Goodyear RoadService App to instantly connect drivers with roadside assistance if needed
- Turnkey retreading for commercial and off-the-road tire casings
- Site audits to enhance tire longevity and performance
- Tire performance monitoring for both commercial and off-the-road tires



COMMERCIAL TRUCK SERVICES THAT HELP FLEETS GO FAR

Goodyear® commercial and off-the-road tire experts are ready to give your fleet a helping hand with services that can help boost your bottom line.

THE MOST RELIABLE NATIONWIDE ROADSIDE SERVICE IN THE INDUSTRY*

Drivers can rely on Goodyear Commercial Tire & Service Network for 24-hour customer support in case of breakdowns. Our roll-time goal of two hours or less helps trucks get back on the road fast.

TIRE SURVEYS AND SITE AUDITS

Goodyear's trained professionals can record tire pressures, tread depths and other key metrics to help fleets make informed decisions about their tire assets.

TRAILER-READINESS INSPECTIONS

Customized reports on essential vehicle systems can help fleets improve safety, avoid unnecessary costs, stay in compliance with CSA (Compliance Safety Accountability) requirements and enhance their fleet's efficiency.

*Fleet research study, Nov. 2015, Lieberman Research Worldwide. 590-fleet sample. Goodyear Dealer network roadside service compared to Michelin, Bridgestone and Continental.



FLEET MANAGEMENT TOOLS TO HELP FLEETS SAVE

Goodyear's powerful set of fleet management tools can help fleet customers streamline their daily time management, improve decision-making processes and find new ways to save money. Any Goodyear® Commercial Tire & Service Network member or fleet sales manager can help.

ONLINE ACCESS TO BUSINESS INTERACTIONS

- Service reporting
- Online service requests
- Retread and casing reporting
- Retread inventory tracking
- Purchase history
- Real-time service updates

CUSTOMIZED VALUE CALCULATIONS

A Goodyear Commercial Tire & Service Network member or fleet sales manager can show fleets how much they can save by using Goodyear technologies and services.

VISUAL REPORTING

Fleets can pinpoint opportunities for improvement with consultations and customized reports on topics such as tire and retread purchases, tire performance, service events and retread stats.

REAL-TIME SERVICE EVENT UPDATES

Goodyear Commercial Tire & Service Network members use technology called the SmartTech App to streamline the road service process and provide real-time updates.

TIRE PERFORMANCE TRACKING

Fleets can track commercial tires with Tire Trac and monitor casings through the retreading process using GTRACS.



TIRE TRAC



GTRACS



GOODYEAR® INNOVATIONS TO HELP REDUCE COSTS



FUEL MAX® TECHNOLOGY

Goodyear tires with Fuel Max Technology can help fleets save money on one of their largest operating costs — fuel. Featuring innovative fuel-saving compounds, tire constructions and tread designs, Fuel Max tires help reduce rolling resistance in every wheel position.



DURASEAL TECHNOLOGY®

The world's first built-in tire sealant for commercial truck tires, DuraSeal Technology helps reduce downtime and costly repairs by keeping trucks moving in the face of nails, screws and sharp objects. Tires with DuraSeal Technology instantly seal punctures up to 1/4" in the face of the tread* to help keep hardworking fleets moving.


*Seals up to 1/4-inch tread punctures only. Does not seal sidewall punctures.



UNICIRCLE® RETREAD TECHNOLOGY

Goodyear can help extend the life cycle of tires with innovative, spliceless UniCircle retreads. Installed with no cutting, UniCircle retreads are uniform and balanced and help fleets get long miles to removal.

STEER/ALL-POSITION



DRIVE



TRAILER



REGIONAL/URBAN

ALL-POSITION



DRIVE



TRAILER

MIXED SERVICE

ALL-POSITION



DRIVE



SUPER SINGLE



Recommended ●
Optional ○



*Available with or without DuraSeal Technology®

TIRES TO MEET YOUR NEEDS.

Goodyear® offers a full line of commercial tires and retreads for long haul, regional, urban and mixed service applications. From advanced toughness to fuel efficiency and more, these tires offer leading-edge benefits that can help fleets reduce operating costs.

Use these charts for a quick view of all the tires available, including each tire's wheel position, application, size and load range.



CATEGORY		LONG HAUL/REGIONAL/URBAN																																										
Tire	Position	Wide Base		Steer/All-Position										Drive										Trailer																				
	Size	Fuel Max™ SSD DuraSeal™	Fuel Max™ SST DuraSeal™	Endurance LHS	Marathon® LHS®	Fuel Max™ RSA	Endurance RSA	Endurance RSA ULT	G949 RSA™ Armor Max®	G159™	G291™	G647 RSS®	G947 RSS™ Armor Max®	G670 RV MRT	G670 RV ULT	Marathon RSA	Marathon RSS	Fuel Max™ LHD G505D™	Endurance LHD	G572 A LHD Fuel Max	G572 1AD Fuel Max™	Marathon LHD	G182 RSD®	G182 RSD GHG	G622 RSD®	Marathon RSD	G633 RSD™	G933 RSD™ Armor Max®	Endurance RSD ULT	Fuel Max™ LHT™	G316® LHT™ DuraSeal + Fuel Max™	G316® LHT™ Fuel Max®	Marathon® LHT™	G619 RST™	G614 RST®	G114™ LHT™								
Light Truck	LT225/75R16							F	F				F																F															
	LT245/75R16							F					F																F															
	LT215/85R16							F	F				F																F															
	LT235/85R16									F			F																												G			
Truck - Tubeless	10R17.5																																										H	
	8R19.5												F															F																
	10R22.5																																											
	11R22.5				G, H	G, H	G, H	G, H													G, H	G, H	G	G	G, H	H	H														G	G	G	G
	12R22.5							H																	H	H																		
	11R24.5				G, H	G, H	G, H	G, H													G, H	G, H		G, H	G, H		H														G	G	G	
	215/75R17.5																																										H	
	225/70R19.5								G					F, G		F												F, G																
	245/70R19.5								H					G		G												G																
	265/70R19.5												G																															
	435/50R19.5																																										L	
	255/70R22.5								H						H		H										H														H			
	275/70R22.5								J						H																											J		
	245/75R22.5								G						G													G																
	265/75R22.5								G						G													G																
	295/75R22.5				G, H	G, H	G, H	G											G	G	G	G	G	G	G		G	G													G	G	G	G
	275/80R22.5														H																													
	295/80R22.5														H																													
	315/80R22.5																	J, L																										
445/50R22.5	L	L																																										
285/75R24.5			G, H	G																G	G		G				G													G	G	G		
Tube-Type	10.00R15																																											J

NOTE: The letters in the chart represent load ranges.



CATEGORY		MIXED SERVICE																									
Position		All-Position														Drive											
Tire	Size	G731™ MSA DuraSeal™	G731™ MSA	G751™ MSA DuraSeal™	G751™ MSA	Endurance™ WHA DuraSeal™	Endurance™ WHA	G296™ WHA® DuraSeal™	G296™ WHA®	G289™ WHA® DuraSeal™	G289™ WHA®	G296™ MSA DuraSeal™	G296™ MSA	G287 MSA®	G288 MSA® DuraSeal™	G288 MSA®	Workhorse MSA	Armor Max Pro Grade MSD	G741 MSD™	G278 MSD®	G282 MSD®	G171™ LT	G971™ Armor Max®	G177™	G177 OTR	Workhorse MSD	
		Lt. Truck	LT215/85R16																								
	LT235/85R16																										
Truck – Tubeless	8R19.5																										
	11R22.5	H	H	H	H												H	H	H		H						H
	12R22.5		H		H														H		H						
	385/65R22.5												J								J						
	425/65R22.5							L	L			L	L								L						
	445/65R22.5												L	L							L						
	255/70R22.5																H										
	275/70R22.5		H																								
	315/80R22.5			L	L	L	L				L	L						L									
	11R24.5		H		H											H		H	H		H						H
12R24.5				H													H									H	
Tube-Type	11.00R20														H												H
	12.00R24															J											J



CATEGORY		REGIONAL/URBAN				MIXED SERVICE					
Position		Steer/All-Position		Drive		All-Position		Drive			
Tire	Size	SP 348®	SP 160™	SP 345®	SP 431A™	SP 461®	SP 831™	SP 231A™	SP 281	SP 881™	
		Truck – Tubeless	225/70R19.5	G				G			
245/70R19.5	G					G					
11R22.5			H		H						
255/70R22.5			H				H				
295/75R22.5			G		G						
315/80R22.5				L							
385/65R22.5								J			
425/65R22.5									L		
11R24.5			H		H						H
285/75R24.5			G								



CATEGORY		LONG HAUL			REGIONAL/URBAN			MIXED SERVICE			
Position		Steer	Drive	Trailer	All-Position	Drive		All-Position	Drive		
Tire	Size	Armorsteel LHS™	KDA®	Armorsteel LHD	Armorsteel LHT	Kelly KRH®	Armorsteel RSA ULT	KDM® I	Armorsteel RSD ULT	Armorsteel MSA	Armorsteel MSD
		Truck – Tubeless	225/70R19.5						G		G
245/70R19.5							G		G		
11R22.5	G		G		G	H		H		H	H
295/75R22.5	G		G	G	G	G		G			
11R24.5	G		G		G	H		H		H	H
285/75R24.5	G		G		G						

NOTE: The letters in the charts represent load ranges.

Long Haul - Steer/All Position

Endurance LHS

A Smartway-Verified, Tough Long Haul Steer Tire for High Miles to Removal

- Wear-resistant tread compound
- Dual-layer tread
- Rigid casing construction
- Computer optimized footprint
- Casing compounds



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	113	51	8.25	11.0	279	41.5	1,054	19.4	493	501	311	18	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	11.0	279	41.5	1,054	19.3	490	501	311	18	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55	8.25	11.1	282	43.4	1,102	20.3	516	479	298	18	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	56	8.25	11.2	284	43.5	1,105	20.4	518	478	297	18	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.0	279	41.5	1,054	19.5	495	501	311	18	12.5	318	75	
285/75R24.5	H	6,780	3,075	120	830	6,175	2,800	120	830	114	52	8.25	11.2	284	41.6	1,057	19.5	495	499	310	18	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75	
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	111	50	8.25	11.3	287	40.4	1,026	18.8	478	514	319	18	12.9	328	75	

Long Haul - Steer/All Position

G399A LHS Fuel Max

Fuel Efficiency Combined With Long Mileage

- Innovative fuel-saving compounds lower rolling resistance
- Outside tread shoulder compound
- Four-belt construction



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	56	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75
285/75R24.5	H	6,780	3,075	120	830	6,175	2,800	120	830	113	51	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.9	328	75
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	111	50	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.9	328	75

Long Haul - Steer/All Position

Marathon LHS

Goodyear's SmartWay®-Verified Long Mileage Steer Tire.

- Enhanced tread compounds
- Five-rib construction
- Pressure distribution groove
- Steel-belt construction
- Lateral grooves and rib edge sipes



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm						
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	56	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75	
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	111	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75	

Long Haul - Drive

Endurance LHD

A SmartWay Verified, Tough Long Haul Drive Tire That Offers High Miles to Removal

- NEW cap base tread combination
- NEW sidewall compound
- Steel belt package
- Shoulder wedge
- Tredlock® Technology



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	126	57	8.25	11.0	279	42.3	1,074	19.9	505	492	306	30	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	126	57	8.25	11.0	279	42.4	1,077	20.0	508	491	305	30	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	140	64	8.25	10.9	277	44.5	1,130	20.9	531	469	291	30	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	140	64	8.25	10.8	274	44.5	1,130	20.9	531	469	291	30	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	137	62	8.25	11.1	282	42.3	1,074	19.9	505	493	306	30	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	131	59	8.25	11.4	290	41.3	1,049	19.3	490	508	316	30	12.9	328	75	

Long Haul - Drive

Fuel Max LHD G505D

Maximize Your MPG With The Goodyear® Fuel Max LHD G505D

- Next-generation fuel-saving compounds
- Tredlock Technology features interlocking microgrooves
- Deep 24/32" tread depth
- Circumferential and lateral tread grooves
- Extra-wide tread



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	121	55	8.25	11.3	287	40.7	1,034	19.0	483	513	319	24	12.9	328	75	

Long Haul - Drive

Fuel Max SSD

Wide-Base Drive Tire for Enhanced Fuel Efficiency and Long Miles to Removal

- Special tread compound
- Optimized tread design and tire footprint
- Tredlock technology
- Wide grooves with stone ejectors
- Open shoulder design
- Built-in DuraSeal Technology



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
445/50R22.5	L	10,200	4,625	120	830	0	0	0	0	190	86	14.00	17.4	442	40.0	1,016	18.5	470	522	324	24	0.0	0	75

Long Haul - Drive

G572 1AD Fuel Max

A Premium Tire For High-Torque, Single Axle Drive and 6x2 Applications That Offers Enhanced Fuel Efficiency, Tread Life and Traction.

- Fuel Max® Technology
- Tredlock® Technology with interlocking microgrooves
- Highly siped center rib and lateral grooves
- Semi-solid shoulder ribs



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	121	55	8.25	11.1	282	42.1	1,069	19.7	500	496	308	24	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	121	55	8.25	11.3	287	40.7	1,034	19.0	483	513	319	24	12.9	328	75

Long Haul - Drive

G572A LHD Fuel Max

A Fuel-Efficient Long Haul Drive Tire With Long Mileage.

- Fuel-saving compounds
- Tredlock® Technology features interlocking microgrooves
- Deep 30/32" tread depth



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	96	44	7.50	10.0	254	37.0	940	17.4	442	561	349	22	11.3	287	75

Long Haul - Drive

Marathon LHD

Goodyear's SmartWay(R)-Verified Long Mileage Drive Tire

- Enhanced tread compounds
- Tredlock® Technology with interlocking microgrooves
- Highly siped center rib and lateral grooves
- Semi-solid shoulder ribs



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	121	55	8.25	11.1	282	42.1	1,069	19.7	500	496	308	24	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	134	61	8.25	11.1	282	44.1	1,120	20.7	526	473	294	24	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.1	282	44.1	1,120	20.7	526	473	294	24	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	124	56	0.00	0.0	0	0.0	0	19.7	500	498	310	24	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	121	55	8.25	11.3	287	40.7	1,034	19.0	483	513	319	24	12.9	328	75	

Long Haul - Trailer

Fuel Max LHT

Trailer Tire That Helps Save Fuel

- Fuel-saving compounds
- Protective shoulder compound
- 12/32" tread depth
- Steel-belt casing construction
- Solid shoulder rib
- Pressure distribution groove
- Circumferential and lateral grooves
- Like-new matching UniCircle retread



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	100	46	8.25	11.2	284	40.1	1,019	18.7	475	514	319	12	12.9	328	75

Long Haul - Trailer

Fuel Max SST

Wide-Base Trailer Tire with Enhanced Fuel Efficiency

- Special tread compound
- Optimized tread design and tire footprint
- Built-in DuraSeal Technology



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
445/50R22.5	L	10,200	4,625	120	830	0	0	0	0	167	76	0.00	0.0	0	0.0	0	18.1	460	526	327	12	0.0	0	75

Long Haul - Trailer

Fuel Max T

Long Haul Trailer Tire

- Multi-radius cavity
- Special tread compound



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
435/50R19.5	L	9,920	4,500	130	900	0	0	0	0	128	58	0.00	0.0	0	0.0	0	16.6	422	569	354	14	0.0	0	62		

Long Haul - Trailer

G316 LHT DuraSeal + Fuel Max

Puncture-Sealing* Tire That Helps Save Fuel.

- Innovative DuraSeal sealant built into the tire
- Fuel-saving compounds
- Protective shoulder compound
- 12/32" tread depth
- Steel-belt construction
- Solid shoulder rib
- Pressure distribution groove
- Circumferential and lateral grooves



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm						
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	107	49	8.25	10.9	277	41.0	1,041	19.0	483	483	300	12	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	105	48	8.25	11.1	282	39.8	1,011	18.6	472	518	322	12	12.9	328	75	

Long Haul - Trailer

G316 LHT Fuel Max

Helps Reduce Rolling Resistance To Promote Fuel Economy.

- Fuel-saving compounds
- Protective shoulder compound
- 12/32" tread depth
- Steel-belt construction
- Solid shoulder rib
- Pressure distribution groove
- Circumferential and lateral grooves



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	101	46	8.25	10.9	277	41.0	1,041	19.0	483	483	300	12	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	108	49	8.25	11.2	284	43.1	1,095	20.1	511	478	297	12	12.5	318	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	87	39	7.50	10.1	257	36.3	922	17.1	434	568	353	13	11.3	287	81
275/70R22.5	J	6,940	3,150	130	900	6,395	2,900	130	900	96	44	7.50	10.5	267	37.5	953	17.5	445	550	342	14	11.9	302	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	103	47	8.25	11.1	282	41.0	1,041	19.1	485	503	313	12	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	100	45	8.25	11.1	282	39.8	1,011	18.6	472	518	322	12	12.9	328	75

Long Haul - Trailer

Marathon LHT

Goodyear's SmartWay(R)-Verified Long-Mileage Trailer Tire

- Fuel-saving compounds
- Protective shoulder compound
- Strong tire construction



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in			mm	32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	100	46	0.00	0.0	0	0.0	0	19.2	488	502	312	12	12.5	318	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	109	49	0.00	0.0	0	0.0	0	20.6	523	478	297	12	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	104	47	0.00	0.0	0	0.0	0	19.7	500	498	310	12	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	97	44	0.00	0.0	0	0.0	0	18.7	475	515	320	12	12.9	328	75		

Long Haul - Trailer

Marathon LHT II

Long Haul Trailer Tire That Delivers Superb Fuel Efficiency And Extended Mileage Performance

- Multi-radius tread shape
- Strong shoulder rib
- Compact tread design
- Specific groove geometry
- Latest tread compound technology
- Enhanced blading



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	L	9,920	4,500	130	900	0	0	0	0	150	68	0.00	0.0	0	0.0	0	19.6	498	492	306	16	0.0	0	68

Regional/Urban - Steer/All Position

Endurance RSA

The Toughness Fleets Need For Regional and Urban Applications

- Intellimax rib technology
- Special tread block geometry
- Innovative tread compound
- Greenhouse gas (GHG) compliancy sizes available



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	109	50	7.50	10.1	257	40.4	1,026	19.0	483	514	319	21	11.4	290	75	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	122	55	8.25	10.8	274	41.9	1,064	19.6	498	496	308	22	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	123	56	8.25	10.8	274	41.9	1,064	19.6	498	496	308	22	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	131	59	8.25	10.9	277	43.9	1,115	20.6	523	473	294	22	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	131	60	8.25	10.9	277	43.9	1,115	20.6	523	473	294	22	12.5	318	75	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	141	64	9.00	11.6	295	43.1	1,095	20.2	513	482	300	22	13.5	343	75	
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	87	39	7.50	9.7	246	37.4	950	17.6	447	555	345	19	11.0	279	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	93	42	7.50	10.0	254	36.7	932	17.3	439	566	352	18	11.3	287	81	
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	101	46	7.50	10.1	257	38.9	988	18.3	465	534	332	20	11.6	295	75	
275/70R22.5	J	6,940	3,150	130	900	6,395	2,900	130	900	105	48	7.50	10.5	267	38.0	965	17.7	450	547	340	19	11.9	302	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	53	8.25	11.3	287	40.6	1,031	19.0	483	512	318	22	12.9	328	75	

Regional/Urban - Steer/All Position

Endurance RSA ULT

Enhanced Toughness and Mileage For Highway and Local Applications

- Innovative tread design with lateral scrub-resistant tread compound
- Deep zigzag sipes and lateral grooves
- Wide grooves to evacuate water
- Reinforced shoulders and steel-steel casing package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	64	29	6.75	8.6	218	32.5	826	15.3	389	639	397	17	10.0	254	87
245/70R19.5	H	4,940	2,240	120	825	4,675	2,120	120	825	74	34	6.75	9.6	244	33.4	848	15.6	396	622	387	18	10.7	272	75
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.3	211	30.5	775	14.3	363	676	420	14	9.9	251	99
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	50	23	6.00	8.8	224	29.4	747	13.8	351	701	436	14	10.2	259	99
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	57	26	7.00	9.9	251	30.8	784	14.5	368	668	415	15	10.8	274	99

Regional/Urban - Steer/All Position

Fuel Max RSA

Goodyear's Best All-Around Tire For Regional Applications

- Fuel Max Tri-layer compound
- Intellimax rib technology
- Super-tensile steel belts
- Unisteel casing construction
- Robust shoulders
- Innovative tread design
- Computer-optimized footprint



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	116	53	8.25	10.9	277	41.8	1,062	19.6	498	497	309	20	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	40.7	1,034	19.0	483	510	317	20	12.9	328	75	
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	115	52	8.25	11.2	284	40.7	1,034	19.0	483	510	317	20	12.9	328	75	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	116	53	8.25	10.9	277	41.8	1,062	19.6	498	497	309	20	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	124	56	8.25	10.9	277	43.8	1,113	20.4	518	474	295	20	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	125	57	8.25	10.9	277	43.8	1,113	20.4	518	474	295	20	12.5	318	75	

Regional/Urban - Steer/All Position

G159A

Long-Wearing Rib Tire For Effective Local And Highway Service.

- Deep tread design
- Tread design
- Superb tread life
- Special buttressed sidewalls on select sizes



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
265/70R19.5	G	5,355	2,430	120	830	5,070	2,300	120	830	81	37	7.50	10.3	262	34.0	864	15.9	404	606	377	16	11.6	295	75	

Regional/Urban - Steer/All Position

G291

Versatile All-Position Tire With Wear And Traction Toughness For Rugged Metro Service.

- Hundreds of precision-shaped tread wedges
- Superb wet and dry traction.
- Great performance in steer or all-wheel positions.
- Unisteel® construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
315/80R22.5	J	8,270	3,750	120	830	7,610	3,450	120	830	132	60	9.00	12.4	315	42.3	1,074	19.7	500	491	305	18	13.8	351	75	
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	132	60	9.00	12.4	315	42.3	1,074	19.7	500	491	305	18	13.8	351	68	

Regional/Urban - Steer/All Position

G647 RSS

Superb Choice For High-Scrub Applications.

- Suggested for extremely fast wear rate applications
- Tread compound
- Circumferential grooves and lateral blades
- Raised sidewall protector ribs
- Sidewall wear indicators
- Tread radius
- M+S stamped



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
225/70R19.5	F	3,640	1,650	660	95	3,415	1,550	660	95	62	28	6.75	8.9	226	32.2	818	15.0	381	640	398	16	10.0	254	75	
225/70R19.5	G	3,970	1,800	760	110	3,750	1,700	760	110	64	29	6.75	8.9	226	32.2	818	15.0	381	640	398	16	10.0	254	75	
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	77	35	7.50	9.5	241	33.2	843	15.4	391	626	389	16	11.0	279	75	
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	60	27	6.00	8.3	211	33.3	846	15.6	396	619	385	13	9.3	236	75	

Regional/Urban - Steer/All Position

G670 RV MRT

Superb Performance And Handling, And Helps Resist Weather Cracking.

- Anti-oxidants and anti-oxidant compounds
- Rubber compounds
- Circumferential grooves
- Notches and sipes
- High-technology belt system
- Tread pattern
- Fuel-efficient casing



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	83	38	7.50	9.5	241	37.0	940	17.3	439	560	348	14	11.0	279	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	86	39	7.50	10.0	253	36.4	925	17.0	432	566	352	14	11.3	287	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	100	690	93	42	7.50	10.0	254	38.4	975	17.9	455	537	334	14	11.6	295	75
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	93	42	7.50	10.4	264	37.6	955	17.4	442	548	341	14	11.9	302	75
275/80R22.5	H	7,160	3,250	125	860	6,610	3,000	125	860	116	53	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.3	312	75
295/80R22.5	H	7,830	3,550	125	860	6,940	3,150	125	860	109	50	9.00	12.1	307	41.3	1,049	19.2	488	499	310	16	13.2	335	75
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	133	60	9.00	12.5	318	42.5	1,080	19.8	503	489	304	16	13.8	351	75

Regional/Urban - Steer/All Position

G670 RV ULT

Superb Performance And Handling, And Helps Resist Weather Cracking.

- Anti-oxidants and anti-oxidant compounds
- Rubber compounds
- Circumferential grooves
- Notches and sipes
- High-technology belt system
- Tread pattern
- Fuel-efficient casing



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	58	26	6.75	8.9	226	32.0	813	14.9	378	644	400	13	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	71	32	7.50	9.7	246	33.0	838	15.3	389	626	389	13	11.0	279	75

Regional/Urban - Steer/All Position

Marathon RSA

Goodyear's Versatile All-Position Tire For Regional and Urban Applications

- High-scrub compound and a robust sidewall
- Treadlock Technology
- Multi-compound layered tread construction
- All-Steel construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	0.00	0.0	0	0.0	0	18.9	480	514	319	21	11.4	290	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	131	60	0.00	0.0	0	0.0	0	20.5	521	473	294	22	12.5	318	75	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	141	64	0.00	0.0	0	0.0	0	20.1	511	482	300	22	13.5	343	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	91	41	0.00	0.0	0	0.0	0	0.0	0	0	0	18	0.0	0	0	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	125	57	0.00	0.0	0	0.0	0	19.5	495	497	309	22	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	120	55	0.00	0.0	0	0.0	0	18.9	480	512	318	22	12.9	328	75	

Regional/Urban - Steer/All Position

Marathon RSS

Goodyear's Tough All-Position Tire Optimized For Steer And Trailer Positions In Regional And Urban Applications

- High-scrub compound
- All-Steel casing construction
- Four wide grooves
- Computer-optimized tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	88	40	8.25	11.2	284	41.5	1,054	19.5	495	501	311	18	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	104	47	8.25	11.3	286	43.6	1,107	20.5	521	476	296	18	12.5	318	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	86	39	7.50	10.0	254	36.6	930	17.1	434	563	350	15	11.3	287	81	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	111	50	8.25	11.2	284	40.3	1,024	18.9	480	515	320	18	12.9	328	75	

Regional/Urban - Steer/All Position

Regional RHS

Ensures Exceptional Mileage And Even Wear Under The Most Demanding Regional Haul Conditions

- High wearable rubber volume
- 3 Double-Rib Design
- Wide Zig-Zag Grooves
- Solid External Shoulder Ribs
- Stone Penetration Protectors
- Wide Bladed Zone
- Staggered Tread Blocks
- regrooving Indicators



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
205/75R17.5	F	3,525	1,600	110	750	3,305	1,500	110	750	59	27	6.00	8.0	203	29.6	752	13.7	348	702	436	16	9.1	231	75	
235/75R17.5	H	4,410	2,000	112	775	4,190	1,900	112	775	63	29	0.00	0.0	0	0.0	0	14.8	376	657	408	18	10.3	262	75	

Endurance RSD ULT

Enhanced Toughness and All-Season Traction on Local Streets and Interstate Highways

- Advanced tread compounding and tire construction
- M+S stamped open tread design with aggressive blading
- Steel-steel casing package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	52	23	6.00	8.8	224	30.6	777	14.4	366	674	419	16	9.9	251	99
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	49	22	6.00	8.8	224	29.6	752	13.9	353	696	433	16	10.2	259	99
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	7.00	9.9	251	30.9	785	14.5	368	667	415	16	10.8	274	99

Endurance TSD

Long lasting, open shoulder drive tire with enhanced traction for Urban applications

- Lower rolling resistance compounds
- Non-directional tread design
- Enhanced rubber volume
- Deep open-lug design
- Tie-bar shoulder and bladed tread pattern



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width			Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																											
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	152	69	0.00	0.0	0	0.0	0	20.1	511	484	301	26	13.8	351	75			

Regional/Urban - Drive

G182 RSD

All-Around Tire For Regional Service.

- Non-directional tread design
- Enhanced rubber volume
- Open lug design
- Tie-bar shoulder and bladed tread pattern
- Deep 28/32" tread depth



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	123	56	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	132	60	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	139	63	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	141	64	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	118	54	8.25	11.3	287	40.8	1,036	19.0	483	512	318	28	12.9	328	75	

Regional/Urban - Drive

G182 RSD GHG

A Fuel-Efficient Tire Ideal For Regional Service

- Lower Rolling Resistance Compounds
- Non-Directional Tread Design
- Enhanced Rubber Volume
- Deep 24/32" Open-Lug Design
- Tie-Bar Shoulder And Bladed Tread Pattern



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width			Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm						
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	125	57	8.25	10.9	277	41.8	1,062	19.6	498	499	310	24	12.5	318	75		

Regional/Urban - Drive

G622 RSD

For Regional And Local High-Scrub Applications.

- Aggressive blading
- Tie-barred shoulders
- Increased wearable tread rubber
- Unisteel construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	7.50	10.2	259	40.6	1,031	19.0	483	512	318	23	11.4	290	75	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	119	54	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	134	61	8.25	11.1	282	43.9	1,115	20.6	523	475	295	26	12.5	318	75	
12R22.5	H	7,390	3,350	830	120	6,780	3,075	830	120	139	63	9.00	11.7	297	43.3	1,100	20.3	516	482	300	26	13.5	343	75	
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	93	42	7.50	9.6	244	37.6	955	17.7	450	552	343	23	11.0	279	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	10.0	254	37.0	940	17.3	439	561	349	23	11.3	287	81	
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	101	46	7.50	10.0	254	38.9	988	18.3	465	534	332	23	11.6	295	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	114	52	8.25	11.2	284	40.8	1,036	19.1	485	512	318	26	12.9	328	75	

Regional/Urban - Drive

G622 RSD ULT

For Regional and Urban Pick-Up And Delivery Applications.

- Aggressive blading
- Tie-barred shoulders
- Increased wearable tread rubber
- Unisteel® construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	62	28	6.75	8.9	226	32.4	822	15.1	384	641	398	19	10.0	254	75		
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	64	29	6.75	9.0	227	32.4	822	15.1	384	641	398	19	10.0	254	87		
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	76	35	6.75	9.7	245	33.5	851	15.6	396	620	385	20	11.0	279	75		

Regional/Urban - Drive

G633 RSD

Traction-Block Tread Pattern For The Regional Drive Position.

- Traction-block design
- Blading pattern
- High-tensile steel casing and belt construction
- Tough rubber compounds



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	62	28	6.00	8.1	206	33.4	848	15.6	396	622	387	16	9.1	231	75

Regional/Urban - Drive

Marathon RSD

A Long-Lasting, Versatile Drive Tire for Long Haul, Regional and Urban Routes

- 28/32" Tread depth
- Solid shoulder ribs
- All-steel construction
- Penetration protectors
- Three deep, wide grooves



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	121	55	8.25	11.0	279	42.2	1,072	19.8	503	495	308	28	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	138	63	0.00	0.0	0	0.0	0	20.6	523	472	293	28	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	126	57	0.00	0.0	0	0.0	0	19.9	505	493	306	28	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	0.00	0.0	0	0.0	0	19.2	488	509	316	28	12.9	328	75	

Regional/Urban - Trailer

G114 LHT

Long, Even-Wearing Trailer Tire For Regional Service

- Solid, rounded shoulder ribs
- Deep, five-rib tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
10R17.5	H	4,675	2,120	115	800	4,410	2,000	115	800	76	35	6.75	9.4	239	33.7	856	15.6	396	612	380	14	10.9	277	75		
215/75R17.5	H	4,805	2,180	125	860	4,540	2,060	125	860	59	27	6.75	8.8	224	30.5	775	14.2	361	676	420	16	10.0	254	75		

Regional/Urban - Trailer

G614 RST

Even Wear In Demanding Trailer Applications.

- Shallow tread
- Solid, rounded shoulder ribs
- Premium casing
- Rib edge sipes and lateral grooves



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
LT235/85R16	G	3,750	1,700	110	750	3,415	1,550	110	750	60	27	6.50	9.5	241	30.7	780	14.4	366	671	417	12	10.8	274	75

Regional/Urban - Trailer

G619 RST

Rugged Construction for Spread Axle Trailers

- Deep 18/32" tread depth
- High Scrub compound
- Robust rib design
- Proven four-belt casing



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	119	54	8.25	10.9	277	41.5	1,054	19.3	490	501	311	18	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	128	58	8.25	11.0	279	43.4	1,102	20.2	513	479	298	18	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	116	52	8.25	11.0	279	41.4	1,052	19.3	490	502	312	18	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	109	49	8.25	11.3	287	40.2	1,021	18.8	478	517	321	18	12.9	328	75

Mixed Service - Steer/All Position

Endurance WHA

Goodyear's Best Waste Haul Tire For Long Miles To Removal

- Dual-Layer Tread Compound
- Deep 24/32" Skid Depth
- Steel Belt and Casing Package
- Optimized Shoulder Design
- Four Wide Circumferential Grooves



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	150	68	9.00	12.5	318	43.1	1,095	20.0	508	484	301	24	14.0	356	68

Mixed Service - Steer/All Position

Endurance WHA DuraSeal

Goodyear's Best Waste Haul Tire For Long Miles To Removal

- Dual-Layer Tread Compound
- Deep 24/32" Skid Depth
- Steel Belt and Casing Package
- Optimized Shoulder Design
- Built-In Duraseal Technology Helps Seal Tread Punctures
- Four Wide Circumferential Grooves
- Matching Retread Available
- **Seals up to 1/4" diameter punctures only in the repairable area of the tread. Does not seal sidewall punctures.



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	156	71	9.00	12.5	318	43.1	1,095	20.0	508	484	301	24	14.0	356	68

Mixed Service - Steer/All Position

G275 MSA

Mixed Service All Position Tire

- Hardworking wraparound tread
- Tread pattern and depth
- Wide footprint
- High-tensile steel belts



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
335/80R20	F	6,395	2,900	80	550	0	0	0	0	131	60	9.00	13.1	333	41.4	1,052	19.1	485	499	310	20	0.0	0	81		
365/70R22.5	G	7,830	3,550	95	660	0	0	0	0	154	70	10.50	14.3	363	42.9	1,090	19.7	500	485	301	20	0.0	0	81		
365/80R20	G	8,270	3,750	95	660	0	0	0	0	163	74	11.00	14.4	366	43.0	1,092	19.8	503	483	300	20	0.0	0	81		

Mixed Service - Steer/All Position

G287 MSA

Superior Over-The-Road Performance.

- High-mileage tread compound and enhanced tread volume
- Wide footprint
- Tread radius
- Tread design
- Penetration protectors
- Steel-belt package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBETYPE TIRES ON TYPE I, II AND III RIMS																									
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	146	66	8.00	11.5	292	43.1	1,095	20.2	513	482	300	22	13.2	335	68	

Mixed Service - Steer/All Position

G288 MSA

Outstanding Performance In Off-Highway Rough Road Conditions.

- A 25/32" tread depth and wide footprint
- Innovative tread compound
- Sturdy 4-rib tread design
- Penetration protectors
- Four steel-belt package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm						
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	92	42	7.50	10.0	254	36.9	937	17.3	439	563	350	22	11.3	287	68	
TUBETYPE TIRES ON TYPE I, II AND III RIMS																									
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	177	80	8.50	12.2	310	48.6	1,234	22.7	577	430	267	25	14.1	358	62	

Mixed Service - Steer/All Position

G288 MSA DuraSeal

Puncture-Sealing* Tire Offering Outstanding Performance In Off-Highway Rough Road Conditions

- Built-in sealant
- A 25/32" tread depth and wide footprint
- Tread compound
- Tread design
- Penetration protectors
- Steel-belt package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	146	66	8.25	11.1	282	44.0	1,118	20.7	526	474	295	25	12.5	318	68

Mixed Service - Steer/All Position

G289 WHA

Offers A 68 MPH Speed Rating And Helps Provide Outstanding Performance In Waste Haul Applications.

- Wider, deeper 24/32 tread
- Waste haul tread compound
- Distinct sidewall protector rib
- Optimized shoulder design
- Four wide circumferential grooves
- Wide footprint



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	152	69	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68

Mixed Service - Steer/All Position

G289 WHA DuraSeal

Puncture-Sealing* Tire That Helps Provide Outstanding Performance in Waste Haul Applications.

- Built-in sealant helps seal tread punctures*
- Wider, deeper 24/32 tread
- Waste haul tread compound
- Distinct sidewall protector rib
- Optimized shoulder design
- Four wide circumferential grooves
- Wide footprint



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	158	72	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68

Mixed Service - Steer/All Position

G296 MSA

Long Mileage Super Single Tire For Heavy On-And Off-Road Applications.

- Deep 23/32" tread
- Severe service compound
- Deep, wide circumferential grooves with more than 500 biting edges
- Optimized tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	J	9,370	4,250	120	830	0	0	0	0	169	76	11.75	14.9	378	42.5	1,080	19.8	503	488	303	23	0.0	0	68
425/65R22.5	L	11,400	5,150	120	830	0	0	0	0	183	83	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	0.0	0	68
445/65R22.5	L	12,300	5,600	120	830	0	0	0	0	206	93	13.00	17.5	445	45.5	1,156	20.9	531	457	284	23	0.0	0	68

Mixed Service - Steer/All Position

G296 MSA DuraSeal

Puncture-Sealing* Super Single Tire Offering Long Mileage For Heavy On- And Off-Road Applications.

- Built-in sealant helps seal tread punctures*
- Deep 23/32" tread
- Severe service compound
- Deep, wide circumferential grooves with more than 500 biting edges
- Optimized tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
425/65R22.5	L	11,400	5,150	120	830	0	0	0	0	196	89	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	0.0	0	68	

Mixed Service - Steer/All Position

G296 WHA

Waste Haul Super Single Tire With A 68 MPH Speed Rating.

- Waste haul tread compound
- Distinct sidewall protector rib
- Deep, wide circumferential grooves with more than 500 biting edges



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
425/65R22.5	L	11,400	5,150	120	830	0	0	0	0	191	87	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	0.0	0	68	

Mixed Service - Steer/All Position

G296 WHA DuraSeal

Puncture-Sealing*, Waste Haul Super Single Tire With A 68 MPH Speed Rating.

- Built-in sealant
- Waste haul tread compound
- Distinct sidewall protector rib
- Deep, wide circumferential grooves with more than 500 biting edges



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
425/65R22.5	L	11,400	5,150	120	830	0	0	0	0	200	91	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	0.0	0	68	

Mixed Service - Steer/All Position

G731 MSA

Offers Brute Strength For Demanding Off-Road Jobs.

- More wearable rubber volume
- Special tread compound
- Wider footprint
- Available with DuraSeal Technology®**



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	135	61	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.1	282	44.0	1,118	20.7	526	474	295	24	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	149	68	9.00	11.8	300	43.2	1,097	20.3	516	484	301	24	13.5	343	68	
255/70R22.5	H	5,510	2,500	830	120	5,070	2,300	830	120	95	43	7.50	10.0	254	37.0	940	17.4	442	561	349	22	11.3	287	68	
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	109	50	7.50	10.6	269	38.1	968	17.7	450	545	339	23	11.9	302	68	

Mixed Service - Steer/All Position

G731 MSA Duraseal

Offers Brute Strength For Demanding Off-Road Jobs.

- High-scrub tread compound and more wearable rubber volume
- Special tread compound
- Wider footprint
- Improved tread design
- Sturdy construction and tread design
- Sturdy, tough casing for retreading
- GHG-compliant rolling resistance



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	143	65	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68	

Mixed Service - Steer/All Position

G751 MSA

Offers Toughness On The Road For Mixed-Service Applications.

- Higher-scrub tread compound and more wearable rubber
- Wider footprint
- Available with DuraSeal Technology®**
- Low rolling resistance construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	135	61	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	66	8.25	11.1	282	44.0	1,118	20.7	526	474	295	24	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	150	68	9.00	11.8	300	43.2	1,097	20.3	516	483	300	24	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	160	72	8.25	11.3	287	45.3	1,151	21.2	538	461	287	24	13.2	335	68	
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	155	70	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68	

Mixed Service - Steer/All Position

G751 MSA Duraseal

Offers Toughness On The Road For Mixed-Service Applications.

- Higher-scrub tread compound and more wearable rubber volume
- Wider tread arc width
- Innovative tread design and compound
- Sturdy, tough casing for retreading
- Wider footprint
- GHG-compliant rolling resistance



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in				mm	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	144	65	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	161	73	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68

Mixed Service - Steer/All Position

Workhorse MSA

All-Position Tire Offering Superior Performance

- High-mileage tread compound and enhanced tread volume
- Wide footprint
- Tread radius
- Tread design
- Penetration protectors
- Steel-belt package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	11.0	279	41.7	1,059	19.5	495	498	310	22	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.0	279	43.7	1,110	20.4	518	475	295	22	12.5	318	68
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	150	68	8.25	11.3	287	45.1	1,146	21.1	536	461	287	22	13.2	335	68
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	142	64	9.00	12.5	318	43.0	1,092	19.9	505	483	300	23	13.8	351	68

Armor Max Pro Grade MSD

Versatile, Long-Lasting Tire for Rugged Mixed Service Applications

- Rugged tread design
- Tough, high-tear compound in the tread
- A special mixed service undertread layer
- Cool-running base compound



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm			32nds	in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																											
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	141	64	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68			
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	149	68	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68			
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	154	70	9.00	11.5	292	43.8	1,113	20.5	521	477	296	33	13.5	343	68			

Mixed Service - Drive

Armor Max Pro Grade MSD DuraSeal

Versatile, Long-Lasting Tire for Rugged Mixed Service Applications

- Rugged tread design
- Tough, high-tear compound in the tread
- A special mixed service undertread layer
- Built-in sealant
- Cool-running base compound



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm				32nds	in	
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	147	67	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	155	70	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68		

Mixed Service - Drive

G171 LT

For Mining, Logging And Rail Yard Applications.

- Tread design and tread rubber compound
- Steel cord casing and steel cord belts
- Heavy undertread
- Enhanced mileage and wear



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	63	28	6.00	8.1	206	33.5	851	15.8	401	620	385	18	9.1	231	75

Mixed Service - Drive

G177

For Rugged Off-Road Conditions Like Coal Fields.

- Rugged tread design
- Tough, high tear compound in the tread
- Four steel-belt package
- Mixed-service undertread compound and a cool-running tread base compound
- Tread depth and cool-running base compound



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	154	70	9.00	11.5	292	43.7	1,110	20.5	521	478	297	33	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	164	75	9.00	11.5	292	45.7	1,161	21.5	546	457	284	33	13.5	343	68	
TUBETYPE TIRES ON TYPE I, II AND III RIMS																									
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	155	70	8.00	11.4	290	43.7	1,110	20.5	521	478	297	33	13.2	335	68	
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	199	90	8.50	12.0	305	49.4	1,255	23.1	587	423	263	40	14.1	358	50	

Mixed Service - Drive

G177 OTR

For Rugged Off-Road Conditions Like Coal Fields.

- Rugged tread design
- Tough, high-tear compound in the tread
- Four steel-belt package
- Mixed-service undertread compound and a cool-running tread base compound
- Tread depth and cool-running base compound



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in			mm	32nds	in	
TUBETYPE TIRES ON TYPE I, II AND III RIMS																									
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	199	90	8.50	12.0	305	49.4	1,255	23.1	587	423	263	40	14.1	358	40	

Mixed Service - Drive

G278 MSD

Tough Super Single Tire for Severe Service Conditions

- Deep 30/32" tread depth
- Criss-cross tread design
- Deep, wide circumferential grooves with more than 500 biting edges
- Open lug design
- Severe service tread compound
- Rugged tread blocks
- High-tensile steel radial casing and strong steel-belt package
- Optimized groove angles



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	J	9,370	4,250	120	830	0	0	0	0	181	82	11.75	14.8	376	43.0	1,092	19.9	505	485	301	30	0.0	0	68
425/65R22.5	L	11,400	5,150	0	0	0	0	830	120	203	92	12.25	16.5	419	44.6	1,133	20.5	521	468	291	30	0.0	0	68
445/65R22.5	L	12,300	5,600	0	0	0	0	830	120	222	101	13.00	18.0	457	46.0	1,168	21.1	536	453	282	30	0.0	0	68

Mixed Service - Drive

G282 MSD

Long On-/Off-Highway Performance.

- Deep 28/32" tread depth
- Tread compound
- Mirrored, non-directional tread design
- Enhanced rubber volume
- Open lug design
- Tie-bar shoulder design and bladed tread pattern



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width			Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm						
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	62	8.25	11.1	282	41.9	1,064	19.6	498	498	310	28	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.1	282	43.9	1,115	20.6	523	475	295	28	12.5	318	75		
12R22.5	H	7,390	3,350	830	120	6,780	3,075	830	120	151	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75		

Mixed Service - Drive

G741 MSD

Rugged Drive Tire for Tough Service

- Deep 33/32" tread with wide footprint
- Aggressive self-cleaning tread design
- Innovative sidewall design
- Cut- and chip-resistant tread compound
- Tread block sipes



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	62	0.00	0.0	0	0.0	0	20.0	508	489	304	33	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	0.00	0.0	0	0.0	0	20.9	531	467	290	33	12.5	318	68

Mixed Service - Drive

G971 Armor Max

Enhanced Toughness For Mining, Logging And Rail Yard Applications.

- Advanced compounds and construction
- Reinforced shoulders and steel sidewalls
- Tread compound
- Tread design
- Heavy undertread



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	52	23	6.00	8.6	218	30.8	782	14.4	366	674	419	17	9.9	251	75
LT235/85R16	E	3,042	1,380	550	80	2,778	1,260	550	80	56	25	6.50	9.5	241	31.1	790	14.5	368	668	415	18	10.8	274	75

Mixed Service - Drive

Workhorse MSD

Mixed Service Drive Tire for On- and Off-Road

- Rugged casing construction
- Deep 31/32" tread with rugged lug configuration
- Advanced tread compound
- Deep undertread
- Steel-belt casing



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	129	58	0.00	0.0	0	0.0	0	20.0	508	490	305	31	12.5	318	62
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	137	62	0.00	0.0	0	0.0	0	20.9	531	469	291	31	12.5	318	62

Regional/Urban - Steer/All Position

SP160

All-Position Tire With Steer Capability For Highway Applications

- Steel-belt package
- Fuel-efficient casing
- Enhanced profile and tread radius
- Hard-rubber bead chafer



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	98	44	8.25	11.1	282	41.1	1,044	19.2	488	505	314	17	12.5	318	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	86	39	7.50	10.0	254	36.5	927	17.0	432	565	351	15	11.3	287	81	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	760	101	46	8.25	11.1	282	41.3	1,049	19.3	490	503	313	17	12.5	318	75	

Regional/Urban - Drive

SP461

Regional Drive Tire

- Traction block tread design
- More Than 400 molded biting edges in the tread
- Tough tread compounds
- Construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	64	29	6.75	8.9	226	32.4	823	15.1	384	641	398	19	10.0	254	75	
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	72	33	7.50	10.2	259	33.2	843	15.5	394	626	389	20	11.0	279	75	

Mixed Service - Steer/All Position

SP231A

All-Position Super Single

- The 20/32" tread depth and five-rib tread
- Sidewall protector ribs



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
385/65R22.5	J	9,370	4,250	120	830	0	0	0	0	161	73	11.75	15.3	389	42.2	1,072	19.6	498	492	306	20	0.0	0	75	

Mixed Service - Steer/All Position

SP281

All-Position Super Single

- Deep 24/32" tread depth and four-rib tread
- Rubber-to-void tread ratio
- Tread groove stone ejectors
- Sidewall protector ribs
- All-position versatility



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
425/65R22.5	L	11,400	5,150	120	830	0	0	0	0	192	87	12.25	16.6	422	44.5	1,130	20.5	521	469	291	24	0.0	0	68

Mixed Service - Steer/All Position

SP345

Regional All-Position Tire For On- And Off-Road

- Five-rib tread design
- All-steel casing



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	132	60	9.00	12.4	315	42.3	1,074	19.7	500	491	305	18	13.8	351	68		

Mixed Service - Steer/All Position

SP831

Mixed-Service All-Position Tire For On- And Off-Road

- Tread compound
- Four steel-belt package
- Tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	91	41	7.50	10.0	254	36.5	927	17.0	432	569	354	19	11.3	287	68	

Mixed Service - Drive

SP881

Mixed-Service Drive Tire For On- And Off-Road

- Tread compound
- Tread groove stone ejectors
- Sidewall protector ribs
- Shoulder



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	138	63	8.25	11.3	287	44.7	1,135	20.9	531	467	290	32	12.5	318	75	

Long Haul - Steer/All Position

Armorsteel LHS

Long Haul Steer Tire Offering Enhanced Fuel Efficiency and Long Miles to Removal

- Uniquely shaped pressure distribution groove
- Barrel-Shaped pressure distribution groove
- Evolving tread pattern
- Smartway® Verified



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	111	50	8.25	10.8	274	41.6	1,057	19.3	490	499	310	18	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	120	54	8.25	11.0	279	44.3	1,125	20.6	523	469	291	18	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	41.6	1,057	19.4	493	499	310	18	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	109	49	8.25	11.1	282	40.5	1,029	18.9	480	513	319	18	12.9	328	75

Long Haul - Drive

Armorsteel KDA

Long Haul Drive Tire Offering A Tough Casing And Many Miles To Removal

- Unique shoulder design
- Deep 28/32" tread depth
- Tread radius
- Stone ejectors
- Unique blading pattern
- All-steel casing and belts



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	122	55	8.25	10.9	277	42.0	1,067	19.5	495	497	309	28	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	128	58	8.25	10.9	277	44.1	1,120	20.5	521	473	294	28	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	125	57	8.25	11.1	282	42.3	1,074	19.9	505	493	306	28	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	8.25	11.1	282	41.1	1,044	19.3	490	508	316	28	12.9	328	75

Long Haul - Drive

Armorsteel LHD

Long Haul Drive Tire Offering Enhanced Fuel Efficiency And Long Miles To Removal

- 26/32" tread depth
- Large, stable blocks
- Circumferential and lateral grooves
- Closed shoulder design



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	0.00	0.0	0	0.0	0	19.3	490	510	317	26	12.9	328	75

Long Haul - Trailer

Armorsteel KTSA

Long Haul Trailer Tire Offering Long Miles to Removal

- Mono-groove tread design
- Unique center groove design
- Low tread void
- Decoupling groove
- Penetration protectors



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	110	50	8.25	10.9	277	41.3	1,049	19.2	488	499	310	13	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	114	52	8.25	11.0	279	43.3	1,100	20.2	513	476	296	13	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	110	50	8.25	11.1	282	41.3	1,049	19.3	490	499	310	13	12.5	318	75

Long Haul - Trailer

Armorsteel LHT

Long Haul Trailer Tire Offering Enhanced Fuel Efficiency and Long Miles to Removal

- Mono-groove tread design
- Unique center groove design
- Low tread void
- Decoupling groove



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	103	47	0.00	0.0	0	0.0	0	19.2	488	499	310	13	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	115	52	0.00	0.0	0	0.0	0	20.2	513	476	296	13	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	105	47	0.00	0.0	0	0.0	0	19.3	490	499	310	13	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	98	45	8.25	11.1	282	40.1	1,019	18.7	475	515	320	13	12.9	328	75

Regional/Urban - Steer/All Position

Armorsteel KRH

All-Position Regional Tire Offering A Long Tread Life

- Deep 20/32" tread
- Tread pattern
- Belt package
- Rib pattern



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	10.9	277	41.5	1,054	19.4	493	501	311	20	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	129	58	8.25	11.0	279	43.5	1,105	20.3	516	478	297	20	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.1	282	40.4	1,026	18.9	480	514	319	20	12.9	328	75	

Regional/Urban - Steer/All Position

Armorsteel RSA ULT

Toughness For Enhanced Service Life In Urban Applications

- Deep tread depth
- Stone ejectors in grooves
- Rugged casing design
- Enhanced shoulder rib



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	63	29	6.75	8.7	221	32.4	823	15.2	386	636	395	16	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	74	33	6.75	9.5	241	33.5	851	15.6	396	615	382	16	10.7	272	75

Armorsteel KDM I

Regional Drive Tire Offering A Long Tread Life And Tough Casing

- Aggressive tread design and deep tread depth
- Isolated-element tread pattern
- Unique blading pattern
- Tread radius
- All-steel casing and belts



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	121	55	8.25	11.0	279	42.1	1,069	19.6	498	496	308	26	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	138	63	8.25	11.0	279	44.1	1,120	20.5	521	473	294	26	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	121	55	8.25	11.3	287	40.9	1,039	19.2	488	510	317	26	12.9	328	75

Armorsteel RSD ULT

Extra Traction And Toughness For Enhanced Service Life In Urban Applications

- Traction block tread design
- More than 400 molded biting edges in the tread
- Tough tread compounds
- Construction



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.7	221	32.5	826	15.3	389	639	397	19	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	72	33	6.75	9.6	244	33.5	851	15.6	396	620	385	20	11.0	279	75

Mixed Service - Steer/All Position

Armorsteel MSA

Mixed Service All-Position Tire for All-Around On- and Off-Road Performance

- Special tread compound
- Innovative tread pattern with 20/32nds tread depth
- Steel belt & casing package
- Tread groove stone ejectors



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	117	53	0.00	0.0	0	0.0	0	19.6	498	497	309	20	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	125	57	0.00	0.0	0	0.0	0	20.4	518	478	297	20	12.5	318	68

Armorsteel MSD

Mixed Service Drive Tire for All-Around On- and Off-Road Performance

- Deep 28/32nds tread depth
- Aggressive lug tread pattern
- Shoulder Tie-bar
- Tough tread compound
- Steel belt & casing package



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	125	57	0.00	0.0	0	0.0	0	19.8	503	495	308	28	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	137	62	0.00	0.0	0	0.0	0	20.4	518	477	296	28	12.5	318	68

LIGHT TRUCK TIRES AND COMMERCIAL TRUCK TIRES

The inflations shown in the load tables are minimum cold pressures for the various loads listed.

LOAD TABLES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES (PSI)

TIRE SIZE		PSI															
		35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110
LT225/75R16	Dual (D)																
	Single (S)																
LT245/75R16	Dual (D)																
	Single (S)																
LT215/85R16	Dual (D)																
	Single (S)																
LT235/85R16	Dual (D)																
	Single (S)																

*For trailer use only.

Note: Letters in parentheses denote load range for which BOLDFACE loads are maximum.

CAUTION – Always use approved tire and rim combinations for diameters and widths.

The Goodyear Tire & Rubber Company periodically updates its product information. To select the proper load and inflation, locate the tire size in the following pages and select the row that matches the maximum load(s) and inflation(s) stamped on the tire. Contact a Goodyear Dealer for tables not listed.

LOAD TABLES

FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES (PSI)

TIRE SIZE	PSI Dual (D) Single (S)	70	75	80	85	90	95	100	105	110	115	120	125	130
		10.00R15TR	D	3660	3830	3980	4130	4300(F)	4470	4640	4805(G)			
	S	3780	3980	4170	4370	4540(F)	4715	4890	5070(G)					
9R17.5HC	D			3525	3635	3745	3860	3970	4080	4190(H)				
	S			3750	3860	3970	4080	4190	4300	4410(H)				
10R17.5	D				3420	3590	3775	3920	4085	4250	4410(H)			
	S				3625	3805	3980	4160	4330	4505	4675(H)			
245/70R17.5*	D					4360	4560	4750	4940	5120	5310	5490	5675(J)	
	S					4620	4820	5020	5220	5420	5620	5810	6005(J)	
205/70R17.5	D		2430	2560	2690	2810	2940	3060	3180	3305(F)				
	S		2590	2730	2870	3000	3130	3270	3400	3525(F)				
215/75R17.5	D	2610	2760	2910	3050	3190	3340	3470	3610	3750(G)				
	S	2770	2920	3080	3230	3380	3530	3680	3820	3970(G)				
215/75R17.5*	D					3490	3645	3800	3950	4100	4245	4395	4540(H)	
	S					3695	3860	4020	4180	4340	4495	4650	4805(H)	
235/75R17.5	D	2880	3040	3200	3360	3520	3670	3830	3980	4130	4190(H)†			
	S	3030	3200	3370	3540	3700	3870	4030	4190	4350	4410(H)†			
8R19.5	D	2460	2610	2755(D)	2865	2975	3085(E)	3195	3305	3415(F)				
	S	2540	2680	2835(D)	2955	3075	3195(E)	3305	3415	3525(F)				
435/50R19.5	S						7720	8040	8360	8680	8990	9300	9610	9920(L)
225/70R19.5	D	2720	2860	3000(E)	3115	3245	3415(F)	3490	3615	3750(G)				
	S	2895	3040	3195(E)	3315	3450	3640(F)	3715	3845	3970(G)				
245/70R19.5	D			3415	3515	3655	3970(F)	4115	4265	4410(G)				
	S			3640	3740	3890	4080(F)	4190	4335	4540(G)				
245/70R19.5	D				3550	3710	3880	4040	4200	4360	4520	4675(H)		
	S				3750	3920	4100	4270	4440	4610	4770	4940(H)		
265/70R19.5	D			3750	3930	4095	4300	4405	4560	4805	4860	5070(G)		
	S			3970	4180	4355	4540	4685	4850	5070	5170	5355(G)		

*For trailer use only.

†Max loads are at 112 psi.

Note: Letters in parentheses denote load range for which BOLDFACE loads are maximum.

CAUTION – Always use approved tire and rim combinations for diameters and widths.

The Goodyear Tire & Rubber Company periodically updates its product information. To select the proper load and inflation, locate the tire size in the following pages and select the row that matches the maximum load(s) and inflation(s) stamped on the tire.

Contact a Goodyear Dealer for tables not listed.

LOAD TABLES

FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES (PSI)

TIRE SIZE	PSI Dual (D) Single (S)	70	75	80	85	90	95	100	105	110	115	120	125	130
		285/70R19.5	D						4805	5005	5205	5405	5600	5790
	S						5145	5360	5570	5785	5990	6200	6405	6610(H)
305/70R19.5	D					4920	5130	5350	5560	5770	5980	6190		6395(J)
	S					5340	5570	5810	6040	6270	6490	6720		6940(J)
9.00R20 10R22.5	D	3860	4045	4230	4410(E)	4585	4760	4940(F)	5075	5210				5355(G)
	S	4080	4280	4480	4675(E)	4850	5025	5205(F)	5360	5515				5675(G)
10.00R20 11R22.5	D	4380	4580	4760	4950	5205(F)	5415	5625	5840(G)	5895	5950			6005(H)
	S	4530	4770	4990	5220	5510(F)	5730	5950	6175(G)	6320	6465			6610(H)
11.00R20 12R22.5	D	4780	4990	5190	5390	5675(F)	5785	5895	6005(G)	6265	6525			6780(H)
	S	4940	5200	5450	5690	6005(F)	6205	6405	6610(G)	6870	7130			7390(H)
12.00R20	D	5440	5680	5910	6140	6360	6610(G)	6790	6970	7160(H)	7390			7610(J)
	S	5620	5920	6200	6480	6740	7160(G)	7380	7600	7830(H)	8050			8270(J)
335/80R20	S	5810	6100	6395(F)										
365/80R20	S			7160	7570	7880	8270(G)							
395/85R20	S			8410	8780	9140	9370(G)	9840	10200	10500(H)	10800	11000(J)	11500	11700(L)
10.00R22 11R24.5	D	4660	4870	5070	5260	5510(F)	5675	5840	6005(G)	6205	6405			6610(H)
	S	4820	5070	5310	5550	5840(F)	6095	6350	6610(G)	6790	6970			7160(H)
11.00R22 12R24.5	D	5080	5300	5520	5730	5840(F)	6095	6350	6610(G)	6790	6970			7160(H)
	S	5240	5520	5790	6040	6395(F)	6650	6910	7160(G)	7380	7600			7830(H)
9R22.5	D	3270	3410	3550	3690	3860(E)	4005	4150	4300(F)	4425	4550			4675(G)
	S	3370	3560	3730	3890	4080(E)	4235	4390	4540(F)	4675	4810			4940(G)

Note: Letters in parentheses denote load range for which BOLDFACE loads are maximum.

CAUTION – Always use approved tire and rim combinations for diameters and widths.

The Goodyear Tire & Rubber Company periodically updates its product information. To select the proper load and inflation, locate the tire size in the following pages and select the row that matches the maximum load(s) and inflation(s) stamped on the tire.

Contact a Goodyear Dealer for tables not listed.

LOAD TABLES

FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES (PSI)

TIRE SIZE	Dual (D) Single (S)	PSI												
		70	75	80	85	90	95	100	105	110	115	120	125	130
445/50R22.5	S			7310	7680	8030	8390	8740	9090	9370	9780	10200(L)		
385/55R22.5	S						7720	8040	8360	8680	8990	9300	9610	9920(L)
295/60R22.5	D						5280	5500	5720	5930	6150	6360	6570	6780(H)
	S						5750	5990	6230	6470	6700	6930	7160	7390(H)
335/65R22.5	S	5430	5700	6005(F)	6220	6475	6780(G)							
385/65R22.5	S			6940	7350	7650	8050	8230	8510	8820	9050	9370(J)		
385/65R22.5*	S						7720	8040	8360	8680	8990	9300	9610	9920(L)
425/65R22.5	S			8270	8740	9100	9370	9790	10100	10500(J)	10700	11400(L)		
445/65R22.5	S			9090	9480	9870	10200	10600	11000	11400	11700	12300(L)		
255/70R22.5	D			3970	4110	4275	4410	4455	4610	4675(G)	4915	5070(H)		
	S			4190	4370	4550	4675	4895	5065	5205(G)	5400	5510(H)		
275/70R22.5	D				4770	4980	5180	5390	5590	5800	6000	6200	6395(H)	
	S				5170	5400	5630	5850	6070	6290	6510	6730	6940(H)	
275/70R22.5	D						4980	5180	5390	5590	5800	6000	6200	6395(J)
	S						5400	5630	5850	6070	6290	6510	6730	6940(J)
315/70R22.5	D						5750	5990	6230	6470	6700	6930	7160	7390(J)
	S						6430	6700	6970	7240	7500	7760	8010	8270(J)
365/70R22.5	S	6385	6700	6940(F)	7310	7610	7830(G)							
245/75R22.5	D	3260	3425	3640	3740	3890	4080	4190	4335	4410(G)				
	S	3470	3645	3860	3980	4140	4300	4455	4610	4675(G)				
265/75R22.5	D	3870	4040	4205	4370	4525	4685	4805(G)						
	S	3875	4070	4255	4440	4620	4800	4975	5150	5205(G)				
265/75R22.5	D	3525	3705	3860	4040	4205	4410	4525	4685	4805(G)				
	S	3875	4070	4300	4440	4620	4805	4975	5150	5205(G)				
295/75R22.5	D	4500	4690	4885	5070	5260	5440	5675(G)						
	S	4500	4725	4940	5155	5370	5510	5780	5980	6175(G)				

*For trailer use only.

Note: Letters in parentheses denote load range for which BOLDFACE loads are maximum.

CAUTION – Always use approved tire and rim combinations for diameters and widths.

The Goodyear Tire & Rubber Company periodically updates its product information. To select the proper load and inflation, locate the tire size in the following pages and select the row that matches the maximum load(s) and inflation(s) stamped on the tire.

Contact a Goodyear Dealer for tables not listed.

LOAD TABLES

FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES (PSI)

TIRE SIZE	Dual (D) Single (S)	PSI												
		70	75	80	85	90	95	100	105	110	115	120	125	130
295/75R22.5	D	4095	4300	4540	4690	4885	5070	5260	5440	5675(G)	5795	6005(H)		
	S	4500	4725	4940	5155	5370	5510	5780	5980	6175(G)	6370	6610(H)		
295/75R22.5	D				4920	5150	5380	5600	5820	6040	6260	6480	6610(H)†	
	S				5330	5580	5820	6070	6310	6550	6780	7020	7160(H)†	
275/80R22.5	D					5080	5305	5530	5750	5965	6185	6400	6610(H)	
	S					5500	5745	5985	6225	6460	6700	6930	7160(H)	
295/80R22.5	D			4855	5100	5335	5570	5805	6035	6265	6490	6720	6940(H)	
	S			5480	5750	6020	6285	6550	6810	7070	7320	7580	7830(H)	
315/80R22.5	D			5170	5430	5680	5930	6180	6430	6670	6910	7150	7390(J)	
	S			6170	6480	6780	7080	7380	7670	7960	8250	8540	8820(J)	
315/80R22.5	D				5260	5510	5750	5990	6230	6470	6700	6930	7160	7390(L)
	S				6670	6980	7290	7600	7900	8200	8490	8790	9080	9370(L)
315/80R22.5	D				5840	6070	6395(G)	6540	6770	6940(H)	7210	7610(J)	7940	8270(L)
	S				6415	6670	6940(G)	7190	7440	7610(H)	7920	8270(J)	8680	9090(L)
315/80R22.5 (HSS) (WHA)	D				5840	6070	6395(G)	6540	6770	6940(H)	7210	7610(J)	8350	9090(L)
	S				6415	6670	6940(G)	7190	7440	7610(H)	7920	8270(J)	9240	10200(L)
12.00R24	D	6120	6390	6650	6910	7160	7390(G)	7610	7830	8050(H)	8300	8540(J)		
	S	6330	6660	6980	7280	7580	8050(G)	8310	8570	8820(H)	9100	9370(J)		
285/75R24.5	D	4540	4740	4930	5205	5310	5495	5675(G)						
	S	4545	4770	4990	5210	5420	5675	5835	6040	6175(G)				
285/75R24.5	D	4135	4340	4540	4740	4930	5205	5310	5495	5675(G)				
	S	4545	4770	4990	5210	5420	5675	5835	6040	6175(G)				

†Max loads are at 123 psi.

Note: Letters in parentheses denote load range for which BOLDFACE loads are maximum.

CAUTION – Always use approved tire and rim combinations for diameters and widths.

The Goodyear Tire & Rubber Company periodically updates its product information. To select the proper load and inflation, locate the tire size in the following pages and select the row that matches the maximum load(s) and inflation(s) stamped on the tire.

Contact a Goodyear Dealer for tables not listed.

NOTES

TOTAL SOLUTION

SEE HOW GOODYEAR® CAN HELP LOWER YOUR OPERATING COSTS WITH THE TOTAL SOLUTION



Trusted Products

Innovative Products
For Any Fleet Application



Nationwide Dealer Network

2,300+ Dealers In North America
Ready To Help Your Fleet



Reliable Services

Most Reliable Nationwide Roadside
Service In The Industry*



Fleet Management Tools

Tire And Retread Tracking
And Fleet Dashboard

FIND YOUR TOTAL SOLUTION

goodyeartrucktires.com

*Fleet research study, Nov. 2015, Lieberman Research Worldwide. 590-fleet sample.
Goodyear Dealer network roadside service compared to Michelin, Bridgestone and Continental.

GOODYEAR
MORE DRIVEN